

## Intermediate maintenance (China) Cayman (987), Cayman S (987) Boxster (987), Boxster S (987) 911 Carrera (997), 911 Carrera S (997) as of 2009 model

Vehicle Ident. No.

Working instruction for order no.

□ Intermediate maintenance

at 30,000, 90,000, 150,000, 210,000 km etc./18,000, 54,000, 90,000, 126,000 miles etc. (Labour operation 03 14 00 ..)

For a description of the various models, see Technical Manual

Note: If the mileage for a regular service is not reached, intermediate maintenance must be carried out after 2, 6, 10..... years.

The term 'checking' includes all necessary subsequent work, such as adjusting, readjusting, correcting and topping up, but does not include repairing, replacing and reconditioning parts or assemblies.

Continued overleaf



## Intermediate maintenance (China) Cayman (987), Cayman S (987) Boxster (987), Boxster S (987) 911 Carrera (997), 911 Carrera S (997) as of 2009 model

Г

	Working instruction	
Vehicle Ident. No	for order no.	
Additional maintenance for spark plugs (Labour operation 03 81 00)		$\checkmark$
Replace spark plugs	every 30,000 km/18,	000 miles or every 4 years
□ Additional maintenance for drive belt		
(Labour operation 03 60 00)		
Check drive belt	every 60,000 km/36,	,000 miles or every 4 years
Check drive belt	-	0,000 miles or every 10 years
Check drive belt	every 240,000 km/1	44,000 miles or every 16 years
Additional maintenance for convertible top		
(Labour operation 03 70 00)		
Service and maintain convertible top (911 Carrera only)	every 30,000 km/18,	,000 miles or every 2 years
□ Additional maintenance every 90,000 km/54,000 m	iles or every 6 years	
(Labour operation 03 83 00)		
Replace drive belt		
Controlled all-wheel (only Carrera 4) : change oil		
PDK transmission: change clutch fluid		
□ Additional maintenance every 180,000 km/108,000	miles or every 12 ye	ears
(Labour operation 03 88 00)		
Manual transmission: change oil		
All-wheel final drive: change oil (911 Carrera only)		
PDK transmission: change transmission oil		
□ Every 2 years		
File condition report for long-life guarantee		
Change brake fluid		
□ Every 4 years		
Replace tyre sealant		
☐ After 4 years, then every 2 years		
Check tyre pressure monitoring system battery		
After 4, 8, 10 years, then every 2 years Ancillary unit mounts and suspension: visual inspection of all ru	bher mountings and bo	ats for damage
	ibber mountings and bot	
Signature (mechanic):		
Test drive:		
Remote control, front seats, footbrake and handbrake (also act	uation travel), engine, cl	utch, steering, transmission, ParkAssist,
cruise control, PSM switch, PASM switch, Sport switch, heating		
Oils, fluids: visual inspection for leaks		
Signature (final check):		

Copyright by Dr. Ing. h. c. F. Porsche AG After Sales Engineering Printed in Germany - 11/08

Porsche Centre