

PORSCHE

Minor maintenance (China) 911 Turbo (997)

Vehicle Ident. No. _____

Working instruction
for order no.

--

Minor maintenance

at 30,000, 90,000, 150,000, 210,000 km etc. / 18,000, 54,000, 90,000, 126,000 miles etc.

(Labour operation 03 24 00 ..)

For a description of the various models, see Technical Manual

Note: If the mileage for scheduled maintenance is not reached, minor maintenance must be carried out after 2, 6, 10..... years.

The term 'checking' includes all necessary subsequent work such as adjusting, readjusting, correcting and topping up, but does not include repairing, replacing and reconditioning parts or assemblies.

	✓
Mix fuel in fuel tank with additive (Keropur from Porsche; Part No. 000 043 206 89)	
Diagnostic system: read out fault memory; reset maintenance interval	
Change engine oil and oil filter (please observe oil change service plan for the 911 Turbo)	
Vehicle underbody and engine compartment: visual inspection for leaks (oils and fluids) and chafing damage (lines and hoses)	
Underbody panels: visual inspection for completeness, secure installation and damage	
Coolant hoses: check condition	
Radiators and air inlets: visual inspection for external contamination and blockage	
Coolant: check level and antifreeze	
Particle filter: replace filter element	
Brake system: visual inspection of the brake pads and brake discs for wear	
Brake hoses and lines: visual inspection for leaks, damage, routing and corrosion	
Drive shafts: visual inspection of the boots for leaks and damage	
Tyres: check condition and tyre pressure	
Check the door locks, lid locks and safety hooks of the front lid to ensure that they are secure and functioning properly	
Vehicle lighting: check operation	
All headlights: check adjustment	
Horn: check operation	
Windscreen wiper/washer system, headlight washer system: check fluid level and nozzle settings, check antifreeze in winter months; check wiper blades	
Electrical equipment, warning and indicator lights: check operation	
Battery: check functional state and fluid level	
Replace spark plugs: see Additional maintenance	

Continued overleaf

PORSCHE

Minor maintenance (China) 911 Turbo (997)

Vehicle Ident. No. _____

Working instruction
for order no.

--

Additional maintenance for spark plugs
(Labour operation 03 81 00 ..)

911 Turbo	every 20,000 km / 12,000 miles or every 4 years	
-----------	---	--

Additional maintenance for drive belt
(Labour operation 03 60 00 ..)

Check drive belt	every 60,000 km / 36,000 miles or every 4 years	
Check drive belt	every 150,000 km / 90,000 miles or every 10 years	
Check drive belt	every 240,000 km / 144,000 miles or every 16 years	

Additional maintenance for convertible top
(Labour operation 03 70 00 ..)

Service and maintain convertible top	every 30,000 km / 18,000 miles or every 2 years	
--------------------------------------	---	--

Additional maintenance every 90,000 km / 54,000 miles or every 6 years
(Labour operation 03 83 00 ..)

Replace drive belt	
Replace fuel filter (911 Turbo only)	
Controlled all-wheel drive (911 Turbo): change oil	

Additional maintenance every 180,000 km / 108,000 miles or every 12 years
(Labour operation 03 88 00 ..)

Manual transmission: change oil	
Automatic transmission: change ATF and ATF filter	
Automatic transmission: change oil in final drive	
All-wheel final drive: change oil	

Every 2 years

File condition report for long-life guarantee	
Change brake fluid	
Check roll-over protection system (911 Turbo Cabriolet only)	
Lubricate adjustment mechanism for Variable Turbine Geometry (VTG)	

Every 4 years

Replace tyre sealant	
----------------------	--

After 4 years, then every 2 years

Check tyre pressure monitoring system battery	
---	--

After 4, 8, 10 years, then every 2 years

Inspect airbag system	
Ancillary unit mounts and suspension: visual inspection of all rubber mounts for damage	

Signature (mechanic): _____

Test drive:

Remote control, front seats, footbrake and handbrake (also actuation travel), engine, clutch, steering, transmission, ParkAssist, cruise control, PSM switch, PASM switch, Sport switch, heating, air conditioning and instruments: check operation	
Oils, fluids: visual inspection for leaks	

Signature (final check): _____